


Minimum breaking load: 70 kN
Short circuit current: 31,5 kA/s
Approximate mass: 8,8 kg

		Seotud projektiga:			
		Kuuste 110 kV siseseviikude ehitamine			
		Joonise nimi Optika tõmbekinnitus			
Joonise number		KPL2410K1_TP_EN-7-01-001		Sidus	
				K.Perillus/30.01.25	
7	GWA-150-20-1M16-0	Ground wire assembly	1	1,0	
6	JB-3	Parallel clamp ø14,1-18,0	1	1,1	---
5	2890012	Dead-end for OPGW ø12,9-14,1	1	2,3	95% RTS OPGW
4	TCB-27-B	Thimble-clevis	1	0,9	120kN
3	353231/300	Double eye, twisted	1	2,3	120kN
2	38138	Shackle	1	0,6	120kN
1	38141/A	Shackle	1	0,6	120kN
LP	CAT. NO.	NAME	QTY.	MASS	REMARKS



BIELSKO-BIAŁA, POLAND
+48 (0) 33 814 50 21
PLP.COM
(PLP POLAND)

CONFIDENTIAL
THIS DRAWING IS THE EXCLUSIVE PROPERTY OF PREFORMED
LINE PRODUCTS COMPANY (PLP) AND IS TO BE USED ONLY WITH
THE PRIOR EXPRESSED PERMISSION OF PLP

NAME
Tension set for OPGWØ 14,1mm

DRAWN:	DATA:	PROJECT	DRAWING NUMBER
T.Pagacz	17-04-23	L352-L353-L356	OPGWT-0564
APVD:	DATA:	SKALA	ARKUSZ Nr
K.Leśnik	17-04-23	1:5	1 Z 1
APVD:	DATA:	MASS	REV
W.Folyn	17-04-23	8,8 [kg]	B