

WRS - Rescue Sled

REF - RBWRS2

Updated 01-2021

Technical Product Data

Technical data	RBWRS3
Length	350 cm
Width	122 cm
Tube width	24.5 cm
Floor Depth	15 cm
Chambers	2 + 1
Valves	3 Leaffield C7 Inflation valves, 3 Leaffield A6 Over Pressure valves
Capacity	5 People - 500 kg calm water 3 People -300 kg swift water
Fabric	Fusion PVC hull, PVC tubes
Weight	20kg excluding valise
Max Tube Pressure	Tubes - 4 psi , Floor - 9 psi
Working Temperature	-30 to +70 celcius
Pack Size	100cm length x 50cm width x 35cm height
Carry Handles	10 Webbing Low Profiles , 1 Rubber Handle
External D Rings	5 x 2 " 316 Stainless Steel
Internal D Rings	4 x 1.3 i" Plastic and elastic rope fitted
Self Rescue Handles	4 Webbing Low Profile
Paddle Holders	2 pairs velcro quick release
Seating	EVA Friction Pads x 2
Identifciation	8 x Reflective strips, RESCUE badge
Standards	ISO 6185-1 , ISO9001 Factory
Warranty	3 year Fabric Warranty

Compatible Accessories

Inflation

Manual Inflation - 4" Barrel Pump **Ref - PWR51**
with
Leaffield valve adaptor (push or screw fit)
Ref - VA200006

or

Compressed Air Inflation - Boat Inflation kit - **Ref - IKWRS1**

Emergency Repair

PVC Fabric repairs using WRS repair kit - **Ref VA200008**
or
Professional Repair service from WRS international

Propulsion

WRS Connector paddle or kayak style doubled bladed paddle **Ref-PEWRS1**
WRS Connector Split paddle or raft style single bladed paddle **Ref-PEWRS2**

Floating External and Internal Grab line

None Required

