# Periskop45 RGB



### Projectors | 3 x powerLEDs 4.5 W DC 500 mA | RGB 77606Z15




























Technical data	
Туре	Surface
Installation position	Wall lights - Ceiling - Floor
Installation environment	Outdoor
Light Source	LED
Circuit structure	powerLEDs
Optics	Spot
Light emission direction	frontal
Nominal power	4.5 W DC
Input voltage range	500mA
CCT / Tone	RGB
C.C. / C.V.	CC
Safety class	3
IP	IP66
IK	IK05
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	Yes
Directional	Swivelling
total angle (vertical plane)	124 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.2 Kg
Electrostatic discharge protection	No
Surge protection	No
Product technological characteristics	Acquastop - TCS

Finishing casing		
Material	Die-cast Aluminium EN AB - 46100	
Colour	Green	
Processing	Open pore anodizing + Powder Coating	

Finishing diffuser	•
Material	Extra clear glass - Tempered
Colour	transparent
Processing	Silk-screening

Finishing bracke	t	
Material	Aluminium 5754	
Colour	Anodised Black	
Processing	15 μm Anodizing	

#### Electronics



C-E500012 DMX-RDM - NFC Multi Channel 4ch. 19~50V DC (1 - 48 art.(48)

Lumen RGBW			
N. Led	Red	Green	Blue
3	80 lm	124 lm	47 lm

## Periskop45 RGB



Projectors | 3 x powerLEDs 4.5 W DC 500 mA | RGB **77606Z15** 

Single emission projectors for outdoor application. The RGB LED light source with a spot light distribution is composed of 3 powerled LEDs.

The device body is made of die-cast aluminium en ab - 46100 and features a green finish, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass - tempered with a silk-screening treatment. The ingress protection degree is IP66; the total weight is of 0.2 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 4.5 W. The power supply cable is included and features a 1 m length.

The device features protection class III and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

### LED Life / Failure Ratio

L70 B10 C0 247450h

# Periskop45 RGB



# Periskop45 RGB | Projectors | Accessories **77606Z15**

150	RF remote control	<b>Code</b> C-W600001
46 50 (36)	Dimmer RF Remote controller	<b>Code</b> <u>C-E700003</u>
1000	Picket - L. 1000mm installation position: land,Cover material: aisi 304 steel	<b>Code</b> C-F500003
700	Picket - L. 700mm installation position: land,Cover material: aisi 304 steel	<b>Code</b> C-F500002
	Bag / Fixing kit - Belt for installation on tree	<b>Code</b> 99802
	Picket installation position: land,Cover material: aisi 304 steel	<b>Code</b> 98550
160	Picket - L. 160mm installation position: land,Cover material: aisi 304 steel	<b>Code</b> 98624