


	
9	25793/U	Wedge tension clamp for ACSR Hawk	1	8,9	120kN
8	AHQ1213	Arcing horn single	1	1,4	---
7	3601	Socket clevis link (IEC size 16)	1	1,1	120kN
6	---	Glass insulator	8	---	---
5	AHU1213	Arcing horn	1	1,1	---
4	3421	Ball-eye link SAB type (IEC size 16)	1	0,6	120kN
3	38821/19	Adjustable extension link 290-440	1	4,5	160kN
2	39170	Double clevis twisted	1	1,4	160kN
1	42218/19	Hinge 105/70/80	1	1,5	210kN
LP	CAT. NO.	NAME	QTY.	MASS	REMARKS

String minimum strength: 120 kN  
Ball/Socket coupling size 16 acc IEC 120  
Mass without insulators: 20,5 kg  
All load carrying steel parts have impact strength  
of 27J/-20° C (test acc. to EN 10045-1)

		Seotud projektiga:  L086 üksikute mastide vahetus				
		Joonise nimi 110 kV tõmbekett 1T-120-34 Joonise number KPL2310K1_TP_EL3-7-01-001 Sidus K.Perillus/28.03.24				
8,9	120kN	 BIELSKO-BIAŁA, POLAND +48 (0) 33 814 50 21 PLP.COM (PLP POLAND)				
1,4	---					
1,1	120kN	CONFIDENTIAL THIS DRAWING IS THE EXCLUSIVE PROPERTY OF PREFORMED LINE PRODUCTS COMPANY (PLP) AND IS TO BE USED ONLY WITH THE PRIOR EXPRESSED PERMISSION OF PLP				
---	---					
1,1	---					
0,6	120kN	NAME  Single tension string 110 kV for ACSR HAWK 21,8mm				
4,5	160kN					
1,4	160kN	DRAWN: DATA: K.Lešnik 20/06/2023		PROJECT L352-L353-L356		
1,5	210kN	APVD: DATA: R.Paterek 20/06/2023		DRAWING NUMBER 110T-2548		
MASS	REMARKS	APVD: DATA: R.Gruszecki 20/06/2023	SKALA 1:10	ARKUSZ Nr 1 Z 1	MASS [kg] see tab.	REW A