



BG Сертификат за съответствие  
CS Prohlášení o shodě  
DA Typeattest  
DE Übereinstimmungsbescheinigung  
EL Πιστοποιητικό συμμόρφωσης  
EN Certificate of conformity  
ES Certificado de conformidad  
ET Vastavastunnistus

FI Vaatimustenmukaisuustodistus  
FR Certificat de conformité  
HU Megfelelőségi nyilatkozat  
IT Certificato di conformità  
LT Atitikties liudijimas  
LV Atbilstības sertifikāts  
MT Ċertifikat ta' konformità  
NL Certificaat van overeenstemming

PL Certyfikat zgodności  
PT Certificado de conformidade  
RO Certificatul de conformitate  
SK Osvedčenie o zhode  
SL Certifikat o skladnosti  
SV Intyg om överensstämmelse


## CERTIFICATE OF CONFORMITY Complete Vehicles

Part 1

The undersigned H. Rihma (Sales Manager) hereby certifies that the vehicle:

0.1.	Make (Trade name of manufacturer)	RESPO
0.2.	Type	110DC
	- Variant	750M351L150
	- Version	2B
0.2.1.	Commercial name(s)	750M351L150
0.2.3.	Identifiers	N/A
0.4.	Vehicle category	O1
0.5.	Company name and address of manufacturer	RESPO HAAGISED AS Tamme 21, Tõrvandi Ulenurme vald 61715 Tartumaa ESTONIA
0.6.	Location and method of attachment of the statutory plates	Front right hand side by means of adhesion
	Location of the vehicle identification number	Front right hand side quadrant
0.9.	Name and address of the manufacturer's representative (if any)	N/A
0.10.	Vehicle identification number	V610110DCSE007803
0.11.	Date of manufacture of the vehicle	02 December 2025

conforms in all respects to the type described in approval e4\*2007/46\*0444\*03 granted on 23 February 2023 and can be permanently registered in Member States having left and right hand traffic and using metric or imperial units for the speedometer and metric or imperial units for the odometer

Place:	Tõrvandi, Estonia
Date:	07 January 2026
Signature:	 H. Rihma

Part 2

### General construction characteristics

1.	Number of axles	1
	Number of wheels	2
1.1.	Number and position of axles with twin wheels	N/A

Main dimensions				
4.	Wheelbase		3315	mm
4.1.	Axle spacing	0 - 1	3315	mm
		1 - 2	N/A	mm
		2 - 3	N/A	mm
5.	Length		5100	mm
6.	Width		1920	mm
7.	Height		973	mm
10.	Distance between the centre of the coupling device and the rear end of the vehicle		5065	mm
11.	Length of the loading area		3500	mm
12.	Rear overhang		1750	mm
Masses				
13.	Mass in running order		317	kg
13.1.	Distribution of this mass amongst the axles		1- 286	kg
13.2.	Actual mass of the vehicle		317	kg
16.	Technically permissible maximum masses			
16.1.	Technically permissible maximum laden mass		750	kg
16.2.	Technically permissible mass on each axle		1- 750	kg
16.3.	Technically permissible mass on each axle group		N/A	kg
17.	Intended registration/in service maximum permissible masses in national/international traffic		96/53/EC	
17.1.	Intended registration/in service maximum permissible laden mass		750	kg
17.2.	Intended registration/in service maximum permissible laden mass on each axle		1- 750	kg
17.3.	Intended registration/in service maximum permissible laden mass on each axle group		N/A	kg
19.	Technically permissible maximum static mass on the coupling point of a semi-trailer or centre-axle trailer		75	kg
Maximum speed				
29.	Maximum speed		140	km/h
Axles and suspension				
30.1.	Track of each steered axle		N/A	mm
30.2.	Track of all other axles		1735	mm
31.	Position of lift axle(s)		N/A	
32.	Position of loadable axle(s)		N/A	
33.	Drive axle(s) fitted with air suspension or equivalent		N/A	
34.	Axle(s) fitted with air suspension or equivalent		No	
35.	Tyre/wheel combination	Tyre	155/80R13 84N	
		Wheel	4Jx13 H2 ET30	
Brakes				
36.	Trailer brake connections		N/A	
Bodywork				
38.	Code for bodywork		DC99	
Coupling device				
44.	Number of the approval certificate or approval mark of coupling device		E1 010510	
45.1.	Characteristic values	D	13,2	kN
		V	-	-
		S	100	kg
		U	-	t
Miscellaneous				
50.	Type-approved in accordance with the design requirements for transporting dangerous goods of UN Regulation No 105 of the Economic Commission for Europe of the United Nations		No	
51.	For special purpose vehicles, designation in accordance with point 5 of Part A of Annex I to Regulation (EU) 2018/858 of the European Parliament and of the Council		N/A	
52.	Remarks: Note to 35: L1 min.79 and SS min.N, higher values are permissible. Alternative tyres: 145 R13 155 R13 155 R13 155R13C 155/80R13 175/70R13 185/70R13C 185R14C 225/75R15			

\*V610110DCSE007803\*