



Mhor: 1:500
Mver: 1:50

KAEVU TÄHIS	SK-15		SKPY-13		SK-24		SK-25		SK-26		SKPY-7		SK-26A	
OLEMASOLEVA MAAPINNA KÕRGUS (m ABS)	60,04		60,10		59,95		60,15		60,52		60,48		60,56	
PROJEKTEERITUD MAAPINNA KÕRGUS (m ABS)	60,04		60,10		59,95		60,15		60,52		60,48		60,56	
TORU PÕHJA KÕRGUS (m ABS)	57,84		57,87		57,92		58,00		58,10		58,80		58,83	
TORU RAJAMISSÜGAVUS	2,20		2,23		2,03		2,15		2,42		1,69		1,73	
LANG	0,003								86,9m		0,004		16,9m	
TORU MATERJAL					PE/PP SN8 De315 - 86,9m						PE/PP SN8 De250 - 16,9m			
VAHEKAUGUSED (m)	9,7		16,1		25,6		35,5				8,4		8,5	
SIRGESTATUD TRASSI PLAAN														

Märkused

1. Torustike asukoht vt joonis VKV-4-02
2. Tingmärgid vt joonis VKV-4-01
3. Ehituskaeviku tüüpristlõiked vt joonis VKV-6-01

[illegible]