



Puuraugu nr	X	Y	Suudme abs kõrgus, m EH2000	Puuraugu sügavus	Katendi paksus, m	Kasuliku kihi paksus, m
EGF 4103						
PA-1/84	6405598,01	688446,45	-	13,0	0,5	8,1
PA-2/84	6405642,79	688367,04	-	9,0	0,4	8,2
PA-3/84	6405547,71	688390,04	-	17,0	0,2	13,3
PA-1104/76	6405565,19	688311,86	-	15,0	0,2	14,8+
EGF 9817						
PA-1/23	6404813,93	688880,77	161,72	17,0	0,3	16,3
PA-2/23	6404512,05	688820,50	154,11	17,0	0,5	16,0
PA-3/23	6404729,05	689171,27	163,34	17,0	0,3	15,4
PA-4/23	6404597,66	688756,11	154,43	17,0	0,3	15,6
PA-5/23	6404701,25	688843,19	153,21	17,0	0,3	14,9
PA-6/23	6404656,02	688950,66	162,21	17,0	0,3	16,7
PA-7/23	6404785,79	689034,80	165,26	17,0	0,3	15,7

0 100 200 m

- Sideehitise kaitsevöönd

Elektripaigaldise kaitsevöönd

Haanja looduspark, Haanja linnuala, Haanja loodusala

III kategooria kaitsealused liigid