

You are here: [Start](#) > [Product groups](#) > [Outdoor lights](#) > [Bollard lights](#) > [Bollard light - Fac...](#)

This item has a predecessor:


DISCONTINUED



Bollard light - Facado A 1,000 mm, 1x
max. 20 W E27, anthracite
Order number: 733018



Image similar



Bollard light - Facado II
angular opal 1,000 mm, 1x
max. 20 W, E27, grey

Order number: 730498
EAN: 4042943179029

199.95 EUR
(VAT included)
per 1

Functions

📄 Data sheet
export

❓ Question / note
about the product

🏢 Brand details

Sales data

| | |
|------------------------|---|
| Minimum order quantity | 1 |
| Order step | 1 |

Description

- IP65 weather resistance
- IP67 connection box suitable for e.g. buried cables 3x1.5 mm²/5x1.5 mm²/3x2.5 mm²
- Newly designed lamp head for improved illumination
- Available with an opal diffuser or a transparent diffuser with smoked glass
- Ideal for e.g. ST64 bulbs and A60/70 bulbs

Our FACADO series bollard lights feature IP65 degree of protection for excellent weather resistance. Choose between an opal diffuser or a transparent diffuser with smoked glass to suit your requirements. The series is available in two different sizes (650 mm/1,000 mm) and features an E27 socket for replaceable lamps. The newly designed lamp head provides even better illumination. The FACADO light is made from high-quality die-cast aluminium and available in dark grey or rust and in square or rounded designs.

The IP67 connection box features a double M20 cable gland suitable for buried cables in sizes 3 × 1.5 mm², 5 × 1.5 mm² or 3 × 2.5 mm², and more.

- Lens height: 113 mm



Features

| | |
|-----------------------------|-----------------------|
| RRP incl. VAT | 199.95 EUR |
| Housing Material | Polycarbonate |
| Housing Material | Aluminium |
| Housing Color | Dark grey |
| Housing Color, Color System | Dark grey RAL 840-M |
| Surface structure | Matt |
| Socket Quantity | 1 PCS |
| max. Power | 1x max. 20.0 W |
| Frequency | 50 / 60 Hz |
| Connection Type | Connectionbox |
| Illuminant Design | ST64 |
| Illuminant Design | A70 |
| Illuminant Design | A60 |
| Product weight | 4000 g |
| Working Temperature | -20 to 40 °C |
| Storage Temperature | -10 to 60 °C |
| Mounting Type | Top mounting |
| Mounting Location | Outside |
| Mounting Area | Bottom panel mounting |

| | |
|-------------------------|---|
| Scope of Delivery | 1x installation material |
| Rated Input Voltage | 220-240 V/AC |
| Power | 20.0 W |
| Control | Dimmable via optional light source |
| Dimmable | Yes |
| Motion Detector | No |
| Through Wiring possible | Yes |
| Protection Class | Protection class I/protective grounding |
| Socket Description | E27 |
| Execution | Without lamp |
| Light direction | Side |
| Light direction | Top |
| Length | 108 mm |
| Width | 108 mm |
| Height | 1000 mm |
| IP Protection Class | IP 65 |

Annexes

File (730495-498_manual.pdf, 710.28 KB)

File (730498_datasheet.pdf, 304.01 KB)

Documents



Operating and mounting accessories



Product Sheet



Light sources - CLA150 E27 DIM 18 W
3,300 K, matt

Order number: 180361

27.95 EUR
(VAT included)
per 1

Light sources - MAS VLE E27 ST64 4 W
1,800 K gold-coloured

Order number: 180359

39.95 EUR
(VAT included)
per 1

