



DigiStreet Micro

BGP760 LED30/757 DPR1 D9

Configuration ID - BGP760I-77148ad9-1967-450a-b14d-580eba3afe1e

Developed with the aim to become your long term partner, the system ready architecture of DigiStreet enables you to enjoy the benefits of connected lighting systems today and also gets the city ready for the innovations to come. Its two sockets enable you to connect directly to the CityTouch system and is also prepared to connect you to the future innovations of IoT. Next to this, each individual luminaire is uniquely identifiable, thanks to the Service tag application. With a simple scan of a QR code, placed on the inside of the mast door, you gain instant access to the luminaire configuration, making maintenance and programming operations faster and easier, no matter what stage of the luminaire's lifetime. DigiStreet is also equipped with dedicated light recipes that: 1) maintain an optimal ecosystem for bats or 2) preserve a dark night sky.

Product data

General Information

Number of gear units	1
Driver included	Yes

Light Technical

Luminous Flux	2730 lm
Luminous Efficacy (rated) (Nom)	153.4 lm/W
Number of light sources	20
Optic type	DPR1
Luminaire light beam spread	115 x 97 °
CIE Code	48 85 99 100 91
Light output ratio	0.91

Operating and Electrical

Input Voltage	220-240
Power Consumption	17.8 W

Controls and Dimming

Driver/power unit/transformer	PSD
-------------------------------	-----

Mechanical and Housing

Dimensions (Height x Width x Depth)	103 X 236 X 627 mm
-------------------------------------	--------------------

Initial Performance (IEC Compliant)

Light source color	5700 K
--------------------	--------

Product Data

Product family code	BGP760
---------------------	--------

Photometric data

