



1	Sprinklermahuti imikaev / Sprinkler tank suction well IK-DN200		Ø1800×4820+250 mm	1
	Klaasplastik (GRP) "Vesmaco Composite", pH 3-10, temperatuuri taluvus max 40°C / Glass-reinforce plastic (GRP) "Vesmaco Composite", pH 3-10, heat resistance max 40°C			
	Maht / Total volume		12000 l	
2	Hoolduskaev / Manhole	GRP	1000×1000 mm	1
3	Luuk / Lockable cover with thermal insulation	Aluminium + PUR	1000×1000 mm	1
4	Ventilatsiooni ühendus / Ventilation pipe	PVC	D110	1
5	Tõsteaas / Lifting loops	EN 1.1121	Tsingitud / Galvinised	2
6	Redel / Ladder with no-slip steps	EN 1.4307/304L	h= 4-4,5 m	1
7	Põhjaklapp / Axial check valve	ENGJL-250	DN200 PN16	1
8	VORTEX tüüpi keerisvoolu pärssija / VORTEX inhibitor	EN 1.4307/304L	D900 H150	1
9	Sissevoolutoru / Inlet pipe	GRP	DN350 PN10	1
10	Väljavoolutoru / Outlet pipe	EN 1.4307/304L	DN200 PN16	1
11	Pöördklapp kiitsiibriga ning teleskoospindliga / Telescopic full-port shut-off/gate valve	Cast iron	DN350 PN10	1
12	Alusplaat / Anchore plate (client's supply)			(1)

Technical reference		Created by		Approved by	
Jevgeni Toom		Maksim Bozhko		Jevgeni Toom	
Title, Supplementary title				A3	1 : 45
Sprinklermahuti imikaev / Sprinkler tank suction well IK-DN200					
Document type		Document status		Date of issue	Rev.
General assembly drawing		Customer drawing		06.09.2023	C 1/1
<b>Vesmaco</b>  Vesmaco OÜ Katusepapi 6, 11412 Tallinn, Estonia www.vesmaco.ee		23051611-IK-DN200-D1800-H4820+250			
		Customer			
		03 TECHNOLOGY OÜ			
		Project			
		Ravila tn. 77, Tartu			

Vesmaco OÜ reserves the right to make unilaterally changes.