

[illegible]

Technical drawing of a building section showing a cross-section of a wall and roof. The drawing includes dimensions in meters (m) and millimeters (mm). Key dimensions include: total height 2.1m, roof slope 1.3m, roof thickness 1.16m, wall thickness 1.4m, roof overhang 1.8m, and total width 4.8m. The drawing is labeled "Tee telg" (ridge beam) and "Sõidutee" (driveway).

Technical drawing of a road intersection. The drawing shows a horizontal road with a vertical road intersecting it. Key dimensions and labels include:

- Tee telg**: Vertical centerline of the intersecting road.
- Sõidutee**: Driving lane of the horizontal road.
- B**: A point or feature on the right side of the intersection.
- Dimensions**:
  - 1,00m - 1,05m: Vertical distance from the horizontal road to the top of the intersection.
  - 1,9m: Horizontal distance from the vertical centerline to the start of the driving lane.
  - 1,16m: Horizontal distance from the vertical centerline to the end of the driving lane.
  - 1,3m: Horizontal distance from the vertical centerline to the point B.
  - 2,1m: Vertical distance from the horizontal road to the top of the intersection.
  - 2,3m: Horizontal distance from the vertical centerline to the start of the driving lane.
  - 4,6m: Horizontal distance from the vertical centerline to the end of the driving lane.
  - 1,4m: Horizontal distance from the vertical centerline to the point B.

Projekteeritud kaitsetoru  
Ø110 (1250N), 20m

Projekteeritud fiiberoptiline kaabel, 95m	
---	--

Leht:  
1/1